

Ultra Slim Ducted

CS-Z25UD3RAW
CS-Z35UD3RAW
CS-Z50UD3RAW
CS-Z60UD3RAW



4-WAY Mini Cassette

CS-Z25UB4RAW
CS-Z35UB4RAW
CS-Z50UB4RAW
CS-Z60UB4RAW



Panel
CZ-BT30EW



CU-Z25UBRA



CU-Z35UBRA



CU-Z50UBRA
CU-Z60UBRA



CZ-RD52CP
(optional for
4-WAY Mini Cassette)



CZ-TACG1**
(optional)

4-WAY Mini Cassette



Technical focus

- WLAN Control Possible (CZ-TACG1 is needed)
- Market-leading Energy Efficiency
- Compact Design (260mm High)
- Easy Installation
- Built-in Drain Pump
- -15°C to +46°C Operating Range

Specifications

Mini Cassette			
2.5KW	3.5KW	4.8KW	5.7KW
CS-Z25UB4RAW	CS-Z35UB4RAW	CS-Z50UB4RAW	CS-Z60UB4RAW
CU-Z25UBRA	CU-Z35UBRA	CU-Z50UBRA	CU-Z60UBRA
2.50 (0.85 - 3.20) 3.20 (0.85 - 4.80)	3.50 (0.85 - 4.00) 4.00 (0.85 - 5.40)	4.80 (0.90 - 5.70) 5.00 (0.90 - 7.10)	5.70 (0.90 - 6.35) 6.00 (0.90 - 8.00)
8,530 (2,900 - 10,900) 10,900 (2,900 - 16,400)	11,900 (2,900 - 13,600) 13,600 (2,900 - 18,400)	16,400 (3,070 - 19,400) 17,100 (3,070 - 24,200)	19,400 (3,070 - 21,700) 20,500 (3,070 - 27,300)
4.55 : 4.16 0.55 (0.24 - 0.82) : 0.77 (0.23 - 1.32)	3.89 : 3.92 0.90 (0.24 - 1.18) : 1.02 (0.23 - 1.65)	3.38 : 3.38 1.42 (0.26 - 1.84) : 1.48 (0.26 - 2.41)	3.29 : 3.30 1.73 (0.26 - 2.20) : 1.82 (0.26 - 2.75)
1 Phase/ 50Hz 230V 240V 2.80 : 3.50 2.50 : 3.40 260 x 575 x 575 18 175 : 180	1 Phase/ 50Hz 230V 240V 4.05 : 4.55 3.95 : 4.35 260 x 575 x 575 18 175 : 195	1 Phase/ 50Hz 230V 240V 6.30 : 6.50 6.10 : 6.30 260 x 575 x 575 18 192 : 197	1 Phase/ 50Hz 230V 240V 7.60 : 8.00 7.40 : 7.80 260 x 575 x 575 18 237 : 253
34 / 25 / 22 : 35 / 28 / 25 50 / 41 / 38 : 51 / 44 / 41	34 / 26 / 23 : 37 / 28 / 25 50 / 42 / 39 : 53 / 44 / 41	38 / 28 / 25 : 39 / 29 / 26 54 / 44 / 41 : 55 / 45 / 42	43 / 32 / 29 : 45 / 32 / 29 59 / 48 / 45 : 61 / 48 / 45
1 Phase / 50Hz 230V 240V 542 x 780 x 289 33 Ø6.35 / Ø9.52 3 - 20 15 -10 ~ +46 : -15 ~ +24	1 Phase / 50Hz 230V 240V 619 x 824 x 299 35 Ø6.35 / Ø9.52 3 - 20 15 -10 ~ +46 : -15 ~ +24	1 Phase / 50Hz 230V 240V 695 x 875 x 320 42 Ø6.35 / Ø12.70 3 - 30 20 -10 ~ +46 : -15 ~ +24	1 Phase / 50Hz 230V 240V 695 x 875 x 320 43 Ø6.35 / Ø12.70 3 - 30 20 -10 ~ +46 : -15 ~ +24

Notes:

The Rated Capacity, Power Input and Running Current are measured in accordance with AS/NZS 3823

• Cooling: Indoor temperature: 27°C DB/ 19°C WB, Outdoor temperature: 35°C DB/ 24°C WB

• Heating: Indoor temperature: 20°C DB/ 15°C WB, Outdoor temperature: 7°C DB/ 6°C WB